

# DA Series

Single and Multi-Tenant  
Entry Security System



For Residential and Commercial Applications

# Features & Benefits

- **Access control**  
Provide entry security for up to four tenants sharing a common entrance
- **Visitor screening**  
Safely and conveniently speak with visitors to determine their intent before unlocking the door
- **Replaces doorbell, easy to install**  
Reduce installation costs by using existing doorbell wire. No doorbell? *No problem!* The system only requires two wires, making installation a snap!
- **Door release powered by system**  
Have the convenience of door release without needing to purchase additional power
- **Simple to use**  
Answer calls and unlock the entrance with simple, intuitive operation
- **Reliable and designed to last**  
Have trouble-free use for years to come, even after the warranty expires!



# Components

## Entrance Stations - Select 1



**DA-1DS**  
1-Call Audio Entrance Station



**DA-2DS**  
2-Call Audio Entrance Station



**DA-4DS**  
4-Call Audio Entrance Station

- Vandal resistant construction
  - Direct select button(s)
  - Backlit directory
  - Connects to door strike
  - Hands-free communication
  - Surface mount
- 6-7/8" H 3-15/16" W 7/8" D

## Master Station & Power Supply



**DA-1MD**  
Audio Tenant Station

- Handset for privacy
- 7-7/8" H  
3-1/2" W  
2-1/2" D



**PT-1211C**  
15V AC Transformer

3-1/16" H  
2-3/8" W  
1-7/8" D

## Box Set - Includes:

- 1 DA-1DS (Door Station)
- 1 DA-1MD (Master Station)
- 1 PT-1211C (Power Supply)



**DA-1AS**  
Single Tenant Box Set



## Accessories



**EL-12S**  
Electric Door Strike

4-1/8" H  
1" W  
1-1/4" D



**DAR-1**  
Call Extension Sounder

4-3/4" H  
3-7/16" W  
1-1/8" D


# Specifications

<b>Power Source</b>	15V AC - use PT-1211C	<b>Door Release</b>	9.5-20V AC, 20Ω or higher resistance - use EL-12S
<b>Communication</b>	Handset (full-duplex)	<b>Calling</b>	Electronic tone with adjustable volume or mute
<b>Wire Type</b>	Door to Tenant: 2-cond., overall shield - use Aiphone #822202 or 2-cond., low cap, PE insulation, solid, non-shielded - use Aiphone #871802 Power to Tenant: 2-cond., low cap, PE insulation, solid, non-shielded - use Aiphone #871802		
<b>Wire Distance</b>	Door Station / Door Strike to Tenant Station / Power Supply (cumulative): 360'(22AWG) 1,020'(18AWG) Power Supply to Tenant Station: 180'(22AWG) 510'(18AWG)		


DA Series Brochure  
08/2015  
Digital Copy



Aiphone Co. Ltd.



Aiphone Corp.



Aiphone Co. Ltd.

The information in this brochure is subject to change without notice.