ROAD SERIES PORTABLE BATTERY POWERED POWERED PA SPEAKERS

let the world be **your stage**!

Designed for maximum portability and versatility the battery powered ROAD series loudspeakers shine in a wide range of mobile applications.

With advanced features such as MP3 or Bluetooth players with USB port, SD card slot and infrared remote control, integrated UHF wireless and comprehensive connectivity the compact ROAD loudspeakers provide a perfect all-in-one solution. For easy coverage extension the series includes a selection of battery powered and passive slave loudspeakers.

- · Battery powered all-in-one loudspeakers
- \cdot Models with built-in Bluetooth players and UHF wireless
- · Slave loudspeakers for extended coverage
- · Maximum mobility with mains independent operation

BATTERY POWERED SPEAKERS ROAD SERIES

ROADJACK BATTERY POWERED BLUETOOTH® SPEAKER WITH MIXER

ALL-IN-ONE SPEAKER

The integrated mixer sports three channels with individual volume controls, a 2-band EQ plus adjustable echo and master volume.

ULTRA MOBILE

A rechargeable battery pack provides up to 20 hours of continuous operation.





READY TO GO

The ROADJACK series powered 2-way system takes your sounds anywhere. With built-in wheels and extension handles for carting convenience.

😵 Bluetooth®

CONNECT ALMOST ANY AUDIO SOURCE

One major feature is a built-in Bluetooth player which permits wireless streaming to the system. It also supports SD card and USB storage devices. The player menu includes multiple genre specific presets for instant EQ adjustment.

EASY OPERATION

The ROADJACK speakers come with a handy IR remote control and convenient stand mount insert.





ROADJACK 8 8" BATTERY POWERED BLUETOOTH LOUDSPEAKER WITH MIXER



ROADJACK 10 10" BATTERY POWERED BLUETOOTH LOUDSPEAKER WITH MIXER

ROADBUDDY BATTERY POWERED BLUETOOTH® LOUDSPEAKER WITH MIXER AND WIRELESS MICROPHONE



CONNECT ALMOST ANY AUDIO SOURCE

The integrated mixer sports three channels with individual volume controls, a 2-band EQ plus adjustable echo and master volume. It delivers up to a stunning 480 watts of Class D peak power and comes in 6" and 10" woofer versions.



TAKE IT EASY

The ROADBUDDY speakers come with a handy IR remote control and convenient pole mount insert.



LESS WIRE. MORE FREEDOM.

The ROADBUDDY incorporates an UHF receiver available with three different frequency bands (863 – 865 Mhz // B5: 584 – 607 MHz // B6: 655 – 679 MHz) and features a slot for an additional unit available as accessory. It comes with a choice of handheld or headset wireless microphones.

VERSATILE MEDIA PLAYER

A major ROADBUDDY feature, the builtin Bluetooth® player also supports USB storage devices and SD cards and includes multiple genre specific presets for instant EQ adjustment.







READY FOR TAKE OFF

A rechargeable battery pack provides up to 8 hours of continuous operation. With built-in wheels and extension handles for carting convenience the ROADBUDDY powered 2-way systems take your sound everywhere.



WIRELESS MICROPHONE AVAILABLE WITH THREE FREQUENCY RANGES:

Standard: 863 - 865 MHz B5: 584 - 607 MHz B6: 655 - 679 MHz







WITH HEADSET MICROPHONE.

ROADBUDDY 10 (B5,B6) BATTERY POWERED BLUETOOTH LOUDSPEAKER WITH MIXER AND WIRELESS MICROPHONE



LDRBUD10BPH2 (B5,B6) BATTERY-POWERED BLUETOOTH SPEAKER WITH MIXER, 2 BODYPACK AND 2 HEADSETS



LDRBUD10HHD2 (B5,B6) BATTERY-POWERED BLUETOOTH SPEAKER WITH MIXER AND 2 WIRELESS MICROPHONES



LDRBUD10HBH2 (B5,B6) BATTERY-POWERED BLUETOOTH SPEAKER WITH MIXER AND WIRELESS MICROPHONE

ROADBOY BATTERY POWERED SPEAKER WITH WIRELESS MICROPHONE

WIRELESS MICROPHONE AVAILABLE WITH THREE FREOUENCY RANGES:

Standard: 863 - 865 MHz B5: 584 - 607 MHz B6: 655 - 679 MHz

ULTRA VERSATILE

CD/MP3 Plaver with Gain and Tone Control, USB & SD Input. 1 x UHF PLL 16 CHN Wireless Unit with dynamic microphone (WS1616MD), optional with beltpack WS1616BP and headset-/ lavaliere microphone available.





ULTRA PORTABLE

Only 5 kg, built in 12 V / 2.9 Ah rechargeable battery, runs up to 5 hours, built in 25 W RMS amplifier, external output for passive box.

LESS WIRE. **MORE FREEDOM.**

The ROADBOY incorporates an UHF receiver available with three different frequency bands (863 -865 Mhz // B5: 584 - 607 MHz // B6: 655 – 679 MHz) and features a slot for an additional unit available as accessorv. It comes with a choice of handheld or headset wireless microphones.

ULTRA EASY

1 x Mic In / Aux In / Aux Out, 2 x sound control (bass/ treble), Talkover function, 100 - 240 V external switch mode power supply.



ROADBOY 65 (B5,B6) PORTABLE PA SPEAKER WITH HANDHELD MICROPHONE



ROADBOY 65 HS (B5,B6) PORTABLE PA SPEAKER WITH HEADSET

ROADBOY 65 SP PASSIVE SLAVE SPEAKER

ROADMAN BATTERY POWERED BLUETOOTH® SPEAKER WITH WIRELESS MICROPHONE

LESS WIRE. MORE FREEDOM.

The ROADMAN incorporates an UHF receiver available with three different frequency bands (863 -865 Mhz // B5: 584 - 607 MHz // B6: 655 - 679 MHz) and features a slot for an additional unit available as accessory. It comes with a choice of handheld or headset wireless microphones.





BATTERY POWERED SPEAKERS

ROAD SERIES

WIRELESS MICROPHONE AVAILABLE WITH THREE FREQUENCY RANGES:

Standard: 863 - 865 MHz B5: 584 - 607 MHz B6: 655 - 679 MHz

PROFESSIONAL AUDIO CONNECTIONS & CONTROLS

XLR/jack combo input for two wired microphones or two Line signal sources (Line / Mic switch), Line in θ out on RCA.

VERSATILITY CHAMPION

The ROADMAN comes with a CD/MP3/USB/SD Player as well as a wireless microphone unit with handheld mic. A second wireless microphone unit is also available in option.



ROADMAN 102 (B5,B6) PORTABLE PA SPEAKER WITH HANDHELD MICROPHONE



ROADMAN 102 HS (B5,B6) PORTABLE PA SPEAKER WITH HEADSET MICROPHONE

ROADMAN 102 SL POWERED SLAVE SPEAKER



ROADMAN 102 SP PASSIVE SLAVE SPEAKER

ROAD SERIES PORTABLE BATTERY POWERED POWERED PA SPEAKERS

SPECIFICATIONS ROADBUDDY:

SPECIFICATIONS ROADJACK:

| Art. No.: | LDRBUD10(HS) |
|--------------------------------|---|
| Product type: | Portable PA speaker |
| Туре: | powered |
| Low/mid driver dimensions: | 10" |
| Woofer magnet: | Ferrite |
| Woofer brand: | Custom-made |
| HF driver dimensions: | 1" |
| HF driver magnet: | Ferrite |
| HF driver brand: | Custom-made |
| Amplifier: | Class D |
| RMS: | 120 W |
| Peak power: | 480 W |
| Frequency range: | 55 - 18,000 Hz |
| Max, SPL: | 115 dB |
| Protection circuits: | overvoltage, short circuit, limiters, DC |
| Controls: | AUX / MP3 Switch, High, Low, Master Volume, Mic 2 Level, Mic 1 Level, CD / Tape IN Level, Echo |
| Indicators: | power, charge/battery status |
| Media player | |
| Supported media: | USB stick, Bluetooth, SD card |
| Supported formats: | MP3, WMA, WAV |
| Media player controls: | Stop, Next track, Previous track, Repeat, Mode (Menu / Bluetooth / SD / USB), Play / Pause, Equalizer |
| Media player display elements: | Lighted multifunctional LC display |
| Line inputs: | 1 |
| Line input connectors: | 3.5 mm jack, 2 x RCA, 2 x XLR, 6.3 mm jack |
| Mic inputs: | 2, XLR, 6.3 mm jack |
| Wireless Unit | |
| Radio Frequency Range | Standard: 863 - 865 MHz B5: 584 - 607 MHz B6: 655 - 679 MHz |
| Modulation Type | analogue FM |
| Channels | 16 |
| Frequency range | 50 - 17,000 Hz |
| Controllers | Power/Volume, Value Up, Value Down, ASC, MUTE-Level (squelch) |
| Indicators | LED display, RF (LED), AF (LED) |
| Connections | TNC for receiver antenna |
| RF Transmitter Power Output | 10 mW |
| Operating voltage: | Switching Power Supply, 100 V - 120 V / 60 Hz, 220 V - 240 V AC / 50 Hz |
| Rechargeable batteries: | 12 V / 5 Ah |
| Cabinet material: | PP black |
| Cabinet construction: | bass reflex |
| Dimensions (W x H x D): | 415 mm x 525 mm x 328 mm |
| | |
| Weight: | 16.5 kg |
| | 16.5 kg IR remote control for media player, carrying handle, 36 mm tripod flange, |

| Art. No.: | LDRJ8 | LDRJ10 |
|--------------------------------|---|---|
| Product type: | Portable PA Speaker | Portable PA Speaker |
| Type: | powered | powered |
| Low/mid driver dimensions: | 8" | 10" |
| Woofer magnet: | Ferrite | Ferrite |
| Woofer brand: | Custom-made | Custom-made |
| HF driver dimensions: | (broad band) 3" | (broad band) 3" |
| HF driver magnet: | Ferrite | Ferrite |
| HF driver brand: | Custom-made | Custom-made |
| Amplifier: | Class D | Class D |
| RMS: | 25 W | 25 W |
| Peak power: | 100 W | 100 W |
| Frequency range: | 90 - 18,000 Hz | 65 - 18,000 Hz |
| Max. SPL: | 113 dB | 117 dB |
| Protection circuits: | short circuit, over-current, overload protection | over-current, short circuit, overload protection |
| Controls: | Master Volume, Mic 2 Level, CD / Tape IN Level, high, Iow, Mic 1 Level, Echo, AUX / MP3 switch | CD / Tape IN Level, low, Mic 1 Level, Mic 2 Level, Master Volume, AUX / MP3 switch, Echo, high |
| Indicators: | Charge/battery status, Power | Power, Charge/battery status |
| Media player | | |
| Supported media: | USB stick, Bluetooth, SD Card | Bluetooth, SD Card, USB stick |
| Supported formats: | WAV, WMA file, MP3 file | MP3 file, WMA file |
| Media player controls: | Play / Pause, Repeat, Next Track, Mode (Menu / Bluetooth /SD / USB), Stop, Previous Track | Play / Pause, Repeat, Next Track, Mode (Menu / Bluetooth /SD / USB), Stop, Previous Track |
| Media player display elements: | Lighted multifunctional LC display | Lighted multifunctional LC display |
| Line inputs: | 1 | 1 |
| Line input connectors: | 2 x RCA, 3.5 mm jack | 2 x RCA, 3.5 mm jack |
| Mic inputs: | 2, XLR / 6.3mm Jack Combo | 2, XLR / 6.3mm Jack Combo |
| Operating voltage: | Switching Power Supply, 100 V - 120 V / 60 Hz, 220 V - 240 V AC / 50 Hz | Switching Power Supply, 100 V - 120 V / 60 Hz, 220 V - 240 V AC / 50 Hz |
| Rechargeable batteries: | 12 V / 5 Ah | 12 V / 5 Ah |
| Cabinet material: | 15 mm MDF | 15 mm MDF |
| Cabinet construction: | vented | vented |
| Dimensions (W x H x D): | 385 mm x 450 mm x 298 mm | 415 mm x 525 mm x 328 mm |
| Weight: | 13.8 kg | 16.2 kg |
| Other features: | Extendable handle, transport handle, transport casters, IR remote for media player, stand mount 36 mm | Stand mount 36 mm, IR remote for media player, transport casters, transport handle, extendable handle |

AVAILABLE ACCESSORIES

ROADJACK 8 PC Roadjack 10 PC

PROTECTIVE COVERS FOR LDRJ8 PROTECTIVE COVERS FOR LDRJ10

AVAILABLE ACCESSORIES

ROADBUDDY 10 PC PROTECTIVE COVER FOR LD ROADBUDDY 10

BATTERY POWERED SPEAKERS

ROAD SERIES

SPECIFICATIONS ROADBOY:

| Art. No.: | LDRB65(HS) |
|--------------------------------|---|
| Product type: | Portable PA Speaker |
| Туре: | powered |
| Low/mid driver dimensions: | 6.5" |
| Woofer magnet: | Ferrite |
| Woofer brand: | Custom-made |
| Amplifier: | Class D |
| RMS: | 25 W |
| Peak power: | 100 W |
| Frequency range: | 80 - 15,000 Hz |
| SPL (1W/1m): | 93 dB |
| Max. SPL: | 110 dB |
| Protection circuits: | short circuit |
| Controls: | Master, Voice priority on / off, Line Gain, Bass, Treble, Power, Mic Gain |
| Indicators: | Charge/battery status, Power |
| Media player | |
| Supported media: | CD-R/W, SD Card, CD-R, Audio-CD, USB stick |
| Supported formats: | WMA-CD, MP3-CD, MP3 file, WMA file, Audio-CD |
| Media player controls: | Program, Folder -, Shuffle, Power / Volume, Previous Track, Next Track, Mode (CD / SD / USB), Folder +, Repeat, mute, Play / Pause, CD ejector, Stop |
| Media player display elements: | Lighted multifunctional LC display |
| Line inputs: | 2 |
| Line input connectors: | RCA |
| Mic inputs: | 1, 6.3 mm Jack |
| Line outputs: | 2 |
| Line output connectors: | RCA |
| Loudspeaker outputs: | 1 |
| Speaker output connections: | 6.3 mm Jack |
| Wireless Unit | |
| Radio Frequency Range | Standard: 863 - 865 MHz 85: 584 - 607 MHz 86: 655 - 679 MHz |
| Modulation Type | analogue FM |
| Channels | 16 |
| Frequency range | 50 - 17.000 Hz |
| Controllers | Power/Volume, Value Up, Value Down, ASC, MUTE-Level (squelch) |
| Indicators | LED display, RF (LED), AF (LED) |
| Connections | TNC for receiver antenna |
| RF Transmitter Power Output | 10 mW |
| Operating voltage: | External 100- 240 V AC switch mode power supply, 15 - 18 V DC, 3 A |
| Rechargeable batteries: | 12 V / 2.6 AH |
| Cabinet material: | polypropylene |
| Cabinet construction: | vented |
| Dimensions (W x H x D): | 200 mm x 300 mm x 230 mm |
| Weight: | 6 kg |
| Other features: | 16 mm stand mount, transport handle |
| | · · · · · · · · · · · · · · · · · · · |

AVAILABLE ACCESSORIES

ROADBOY 65 B TRANSPORT BAG FOR LDRB65 AND LDRB65HS

SPECIFICATIONS ROADMAN:

| Art. No.: | LDRM102(HS) |
|--------------------------------|---|
| Product type: | Portable PA Speaker |
| Туре: | powered |
| Low/mid driver dimensions: | 10" |
| Woofer magnet: | Ferrite |
| Woofer brand: | Custom-made |
| HF driver dimensions: | 1" |
| HF driver magnet: | Ferrite |
| HF driver brand: | Custom-made |
| Amplifier: | Class D |
| RMS: | 80 W |
| Peak power: | 320 W |
| Frequency range: | 70 - 16,000 Hz |
| SPL (1W/1m): | 95 dB |
| Max. SPL: | 115 dB |
| Protection circuits: | short circuit |
| Controls: | Power, Line Gain, Treble, Master, Audio-link slave volume, Speech / music switch (Mic / Line 1), Tape volume, Value Down, Voice priority on / off, Volume Mic 2, Volume Mic 1, Audio-link set (master / slave), Speech / music switch (Mic / Line 2), Bass |
| Indicators: | Power, Charge/battery status |
| Media player | |
| Supported media: | USB stick, CD-R/W, CD-R, SD Card, Audio-CD |
| Supported formats: | MP3-CD, Audio-CD, WMA-CD, WMA file, MP3 file |
| Media player controls: | mute, Mode (CD / SD / USB), Previous Track, Stop, Play / Pause, CD ejector, Power / Volume, Program, Folder +, Folder -, Next Track, Repeat, Shuffle |
| Media player display elements: | Lighted multifunctional LC display |
| Line inputs: | 3 |
| Line input connectors: | 2 x RCA, Audio-link input XLR, female |
| Mic inputs: | 2, XLR, 6.3 mm Jack |
| Line outputs: | 3 |
| Line output connectors: | 2 x RCA, Audio-link output XLR, male |
| Loudspeaker outputs: | Speaker Out Unswitched, Speaker Out Switched |
| Speaker output connections: | 6.3 mm Jack |
| Wireless Unit | |
| Radio Frequency Range | Standard: 863 - 865 MHz B5: 584 - 607 MHz B6: 655 - 679 MHz |
| Modulation Type | analogue FM |
| Channels | 16 |
| Frequency range | 50 - 17.000 Hz |
| Controllers | Power/Volume, Value Up, Value Down, ASC, MUTE-Level (squelch) |
| Indicators | LED display, RF (LED), AF (LED) |
| Connections | TNC for receiver antenna |
| RF Transmitter Power Output | 10 mW |
| Operating voltage: | transformer, 24 V DC - 32 V DC (5A), 200 V AC - 250 V AC |
| Rechargeable batteries: | 2 x 12 V / 4.5 AH |
| Cabinet material: | aluminium, plastic |
| Cabinet construction: | vented |
| Dimensions (W x H x D): | 355 mm x 610 mm x 315 mm |
| Weight: | 19 kg |
| Other features: | Stand mount 36 mm, audio-link function, cassette player available optional- ly, transport handle, transport bag available optionally, additional radio receiver (LDRM102R) available optionally, trolley handle, transport casters |

AVAILABLE ACCESSORIES

ROADMAN 102 BAG PROTECTIVE COVER FOR LDRM102 PORTABLE PA SPEAKER