

## RCF CS 3082 Slimline Column Speaker



CS 3082 is formed in an ultra slimline design offering minimal visual impact.

Easy installation can be achieved with either the supplied 'L' shaped wall brackets or the optional AC WM-CS swivel bracket, which allows the installer to angle the speaker to suit.

The new CS Slimline Columns have been optimised for speech reproduction using extended range 2 inch speakers and 1 inch tweeters.

- Ideal for speech reproduction, shape designed to enable corner installation
- Music power/RMS: 60/30W
- Eight 50 mm (2") diameter extended range speakers and two tweeter 25 mm (1")
- Body in extruded aluminium bake-painted RAL 9016 White and front metal grille RAL 9016 White, includes accessory for wall mounting
- Built-in multi-tapped transformer (30 - 20 - 10 W) for 100 V constant voltage connection
- 8 Ohm input that can be selected on the terminal block
- Audio connection on screw terminal block

#

#

**ACOUSTICAL SPECIFICATIONS**

Frequency Response (-10dB): 200 Hz ÷ 20000 Hz

Max SPL @ 1m: 106 dB

Horizontal coverage angle: 180°

Vertical coverage angle: 30°

System Sensitivity: 91 dB

**POWER SECTION**

Nominal Impedance: 8 ohm

Power Handling: 30 W RMS

Peak Power Handling: 120 W PEAK

Recommended Amplifier: 60 W

**TRANSDUCERS**

Dome Tweeter: 2 x 1.0"

Woofer: 8 x 2.0"

**INPUT/OUTPUT SECTION**

Input connectors: Screw Terminals

Output connectors: Screw Terminals

Constant Voltage Transformer: 100 V

Power selection 1: 30 W - 333 ohm

Power selection 2: 20 W - 500 ohm

Power selection 3: 10 W - 1000 ohm

**STANDARD COMPLIANCE**

CE marking: Yes

**PHYSICAL SPECIFICATIONS**

Cabinet/Case Material: Aluminium

Hardware: Wall mount bracket

Grille: Steel

Colour: White - RAL 9016

**SIZE**

Height: 670 mm / 26.38 inches

Width: 78 mm / 3.07 inches

Depth: 66 mm / 2.6 inches

Weight: 2.7 kg / 5.95 lbs

#